



# Pro Dual Direct Drive + Direct Drive 3D Printer

Specifications	NX Pro Dual Direct Drive + Direct Drive	BIGFOOT 200 Pro Dual Direct Drive + Direct Drive	BIGFOOT 350 Pro Dual Direct Drive + Direct Drive	BIGFOOT 500 Pro Dual Direct Drive + Direct Drive	
<b>Build Volume</b>	295x200x200 mm	500x500x200 mm	500x500x350 mm	500x500x500 mm	
<b>DUAL Printing</b>	295x200x200 mm	500x500x200 mm	500x500x350 mm	500x500x500 mm	
<b>Mirror Printing</b>	145x200x200 mm	250x500x200mm	250x500x350mm	250x500x500 mm	
<b>Independent Extruders</b>	Yes	Yes	Yes	Yes	
<b>Packing Size</b>	605x501x500 mm	1006x940x735 mm	1006x940x885 mm	1006x940x1035 mm	
<b>Gross Weight</b>	32 kg	100 kg	120 kg	140 kg	
<b>Printer Size</b>	550x440x410 mm	860x720x510 mm	860x720x660 mm	860x720x810 mm	
<b>Printer Weight</b>	30 kg	68 kg	75 kg	82 kg	
<b>Optimized Materials</b>	ABS, ASA, NYLON, PET-G, PLA, PP, XT-CF20, TPU, PLA-3D870, PVA				
<b>Nozzle Diameter (mm)</b>	0.2 - 0.4 - 0.6 - 0.8 - 1.2 mm	0.4 - 0.6 - 0.8 - 1.2 mm	0.4 - 0.6 - 0.8 - 1.2 mm	0.4 - 0.6 - 0.8 - 1.2 mm	
<b>Layer Resolution</b>	10µm				
<b>Maximum Layer Size</b>	0,2 nozzle: 0.16mm	0,4 nozzle: 0,3mm	0,6 nozzle: 0,48 mm	0,8 nozzle: 0.6 mm	1,2 nozzle: 0.9mm
<b>Extruder Temperature</b>	300°C				
<b>Nozzle Heating Time</b>	20°C: 200°C - 1'15" / 250°C -1'50" / 300°C -2'35"				
<b>Build Plate Leveling</b>	-Automatic				
<b>Heated Bed</b>	100°C				
<b>Power</b>	Energy Smart Management. Power Rating: 500W. Noise Level: 44 dB (closed door, 40dB)				
<b>Display</b>	5"color touch screen. Control devices: PC, tablet, Smartphone. Control mode: Web				
<b>Software</b>	Simplify3D Professional Software				
<b>Connectivity</b>	Connected to network, USB, Wifi, Micro SD card, Ethernet (optional)				
<b>Warranty Period</b>	1 Year Limited Warranty				